# PROCEEDING

INTERNATIONAL CONFERENCE ON INFORMATION TECHNOLOGY AND ENGINEERING APPLICATION 2015

# IT and Engineering for Better life



Proceeding International Conference on Information Technology and Engineering Application

Published by: Penerbit : PPP-UBD Press

#### **CONFERENCE COMMITTEE**

Muhammad Izman Herdiansyah, PhD, Universitas Bina Darma,
IndonesiaErna Yuliwati, PhD, Universitas Bina Darma, Indonesia
Dr. Sunda Ariana, M.Pd., M.M. Universitas Bina Darma, Indonesia
Dr. Ahmad Syarifuddin, M.T., Universitas Bina Darma, Indonesia
Prof. Ahmad Fauzi Ismail. P.hD, Universiti Teknologi Malaysia.
Eric H Zhao, Institute & Multimedia Security Laboratory, Kyushu University
William Benton Wedeking, USA
Prof. Dr. Aizaini Maarof, Universiti Teknology Malaysia.
Prof. Dr. Wan Nasir, Universiti Teknology Malaysia.
Prof Dr. Eko Indrajit, Higher Education Association Information And
Computer Science (APTIKOM), Indonesia
Prof Zainal A Hasibuan, PhD, Higher Education Association Information
And Computer Science (APTIKOM), Indonesia
Dr. Paulus Sukapto, Ir., MBA, Universitas Katolik Parahyangan,
IndonesiaDr. Ir. T. Ari Samadhi, Institut Teknologi Bandung, Indonesia.

#### **REVIEWER & EDITOR**

Leon Andretti Abdillah Darius Antoni Dedy Syamsuar M. Izman Herdiansyah Edi Surya Negara

Support by. Bina Darma University Steering Committee ICIBA Cover Design by. Deni Erlansyah Printed in Palembang, Indonesia, Febuari 2016

## CONTENTS

No	Titel	Page
INF	ORMATION TECHNOLOGY	
1.	Application of 36 Cell Zachman Framework for Integrated Spatial Planning Tax On Dinas Pendapatan Daerah Kota Palembang <b>Paisal, M. Izman Herdiansyah, Afriyudi</b>	1 - 5
2.	Design of Security Systems Cabin Car From Danger Gas CO (Carbon Monoxide) With SMS Gateway Information and Data Logger Slamet Widodo, Ahyar Supani	6 - 14
3.	Implementation Felder Silverman Learning Style Model for Content Support based on Ontology in Indonesia Learning Management System <b>Bernard R. Suteja</b>	15 - 21
4.	Steganography Application Bitwise Method of Encrypted Message with Vigenere Cipher Nazori Agani, Charles Victor B. Saragih, Chris Simon	22 - 31
5.	Vector Machine Learning Method for Text Mining Indonesian Social Media Named Entity Recognition Agus Suryana, Sri Ipnuwati	32 - 37
6.	Software Quality Assurance of Learning Game Using Deutsch and Willis Method Jumdapiokta, Sunda Ariana, Alex Wijaya	38 - 45
7.	Implementation Felder Silverman Learning Style Model for Content Support based on Ontology in Indonesia Learning Management System Adelin, Muhammad Izman Herdiansyah, Afriyudi	46 - 54
8.	Characteristics of Users Website Kopertis II Palembang Eka Hartati, Lin Yan Syah, Linda Atika	55 - 60
9.	Analysis of Factors Affecting the Use of Google Classroom to Support Lectures Andri Wijaya	61 - 68

	Aan Restu Mukti, Zainuddin Ismail, Edi Surya Negara	
	Using Dual-Stack Technique	
22.	Performance Analysis for Migration Method IPv4 to IPv6	148 - 154

# **ENGINEERING APPLICATION**

23.	Design of Plastic Mulch Hole Maker to Decrease Work Load and Increase Work Speed Strawberry Farmer in Bali M. Yusuf, Nyoman Adiputra, I Dewa Putu Sutjana, Ketut Tirtayasa	156 - 160
24.	Design of Baby Walking Assistant (AB3) by Using Axiomatic Design Method <b>Dian Janari</b>	161 - 169
25.	Design Push Up DetectorUsing Quality Function Deployment Method and Anthropometry <b>Ch Desi Kusmindari, Yanti Pasmawati, Ari Muzakir</b>	170 - 175
26.	Flow Pattern in the Estuary of Musi River Using MIKE-21 Flow Model Achmad Syarifudin, Eka Puji Agustini	170 - 180

# Flow Pattern in the Estuary of Musi River Using MIKE-21 Flow Model

### Achmad Syarifudin, Eka Puji Agustini

1 Faculty of Vocation, Bina Darma University 2 Faculty of Computer Science, Bina Darma University Jalan AhmadYani No.3, Plaju,Palembang e-mail: syarifachmad6080@yahoo.co.id, eka\_puji@binadarma.acid

#### Abstract

Musi river is the largest river in Palembang with a length of more than 750 kilometers and an average width of 540 meters where the maximum width of 1,350 meters is located around the Kemaro island. Basically, sedimentation in the Musiriver does include sedimentation due to the high level meeting between the Musi river currents and ocean currents in the Bangka Strait. The silting condition of Musi river is getting more severe because of the sludge that reaches about 40 cm per month. In fact, the volume of sludge could reach 2.5 million meter. There are 13 siltingpoints along the Musi river shipping channel from the BoomBaru port to Bangka Strait. Four points are already very vulnerable because of the silting reaches up to 4 meters. The location which is quite compressis from the northern Payung Island to te estuary, while the location of the worst silting among others is on the outside verge of the Jaranstrait and the water groove of the southern part of the Payung island sedimentation reaches 7 km, so the boat that crosses the groove of Musi river should be guided against the tide that occurs. This research was conducted by using the approach of software models MIKE 21 Flow Model and the results obtained from this study is the pattern of movement of the flow between the other directions and speed of currents and hydrodynamic model of the depth of the river starting from the outside verge to the Musi river which affected the down tide.

Keywords: Pflow pattern, Musi River, Mike-21, Flow model

#### **1 INTRODUCTION**

Musiriver is the largest river in Palembang with a length of more than 750 kilometers and an average width of 540 meters where the maximum width of 1,350 meters is located around the Kemaro island and the minimum width of 250 meters located around the MusiII Bridge. Musiriver has two islands, namely Kembaro (Kemaro) and Kerto islands. The three other major riversare the Ogan river with an average width of 236 meters, Oganriver with an average width of 211 meters and the Keramasan river with an average width of 103 meters [1]. Musiriver is not only used by people around the course but also by big companies locatedalong the Musi river. They use the Musiriver to deliver the products and bring in the raw material through the vessel. There are so many big ships and even very large pacing in the Musi river. Some companies located along the Musiriverare PT. Pertamina, PT. Sriwijaya fertilizer (PUSRI), WilmarGroup and the Port of Boom Baru, and Port at 35 ilir. The role of the Musiriver is very vital and this so called pulse of Palembang city is nowhauntedby various problems. One of the problems is the river silting which continue to increase every year. Of course this is very detrimental to the Government of South Sumatra Province, especially at this time of South Sumatra province being intensively attracts investors to invest in the business sector. Basically, sedimentation in the Musiriver does include a high level of sedimentation caused by the current meeting between Musi river and ocean currents in the Bangka Strait.

The silting condition of Musi river is getting more severe because of the sludge that reaches about 40 cm per month. In fact, the volume of sludge could reach 2.5 million meter. There are 13 silting points along the Musi river shipping channel from the Boom Baru port to Bangka Strait. Four points are already very vulnerable because of the silting reaches up to 4 meters. The location which is quite compressis from the northern Payung Island to the estuary, while the location of the worst silting among others is on the outside verge of the Jaran strait and the water groove of the sedimentation in the southern part of the Payung island reaches 7 km, so the boat that crosses the groove of Musi river should be guided against the tide that occurs.

#### 2 RESEARCH METHODHOLOGY

This study was carried out with the modeling and simulation of flow patterns and sediment transport in water area of the Bangka Strait in position 2.07 - 2.38 of South Latitude and 104.85 - 105.17 of East Longitude. The research location [2, 3] is in figure 1.



Figure 1: Map of Research Location.

#### 2.1 Tools and Materials

The tools used in this research are as in Table 1 below

Table 1: List of tools used in the study						
No	Name of Tools	Number of Uses				
1	Stationery 2 pieces	Writing to recording data				
2	Computer (RAM 2 GB) 1 unit	Performing general modeling				
3	Printer 1 unit	Displaying form of report				
4	Software MIKE-21 Model, MS-Excel	Performing modeling and data processing				
5	Dongle (licensed program) 1 pieces	Activating the software MIKE-21 ${\rm FM}$				
6	Laptop and Printer 1 pieces	Assisting to preparing reports				

The data used in the analysis are as shown in Table 2.

Table 2: Factors and Willis Deutsch						
No	Data properties	Data type	Sources	Units		
1	Tidal	Primary	Field	m		
2	Bathymetry	Secondary	Bakosurtanal/Pelindo	m		
3	The direction and speed of current	Primary	Field	(o ) & m/s		
4	River capacity	Primary	Field	m3/s		
5	The direction and speed of wind	Secondary	BMG	(o) & m/s		
6	Base of Sediment	Primary	Field	mm or		
7	The concentration of suspended sediment	Primary	Field	$\mathrm{mm/l}$		
8	Discharge of sediment from the river	Primary	Field	gram/s		





Figure 2: The hydrodynamic model of the river water velocity direction

#### 2.2 MIKE-21 FM Simulation

MIKE-21 Hydrodynamic Module (HD Module) is a mathematical model to calculate the hydrodynamic behavior of the water against a wide variety of styles functions, for example, certain wind conditions and water levels are specified in the open model of the boundary. HD module simulates the water level and the current differences in the various styles function in lakes, estuaries, and beaches [4, 5].

#### 3 RESULTS AND DISCUSSIONS

After all the boundary condition is discussed in the modeling, the results of global model output on the outside verge of the Musi river are as in figure 2, figure 3 and figure 4 below.



Figure 3: Model hydrodynamic surface elevation watersheds



Figure 4: The total depth of the hydrodynamic model of river flow

#### 4 CONCLUSSIONS AND RECOMMENDATIONS

From the analysis of thestudy, it can be summarized that:

- 1. Greatest speed direction occurred on the Musi river bank ranges between 300-350 degrees.
- 2. Thresold elevation of the outer surface of the Musiriver ranges between 0.20 m 0.40 m will affect the free area for ships to perform well and safe movement.
- 3. The total depth of water occurs at 15-30 m and therefore contributes to the flow of the ship movement into the Musiriver as a whole.
- 4. As a recommendation of this study, it is necessary to study more detail about the correlation of sediment movement and move of the ship to the amount of sediment in the Musi river [6].

Acknowledgments. I would like to say thank you to Prof. Ir. Bochari H. Rachman, M.Sc, Rector of Bina Darma University, Prof. Dr. H. Zainuddin Ismail, MM, Vice Rector I and Dr. Sunda Ariana, M.M., M.Pd., Vice Rector II of Bina Darma University who are pleased to give permission and assistance to the author, especially in the preparation of the data so that the paper can be completed.

#### References

Π

- [1] Anonymous, Department of Public Works BM & NRM Palembang, 2012.
- [2] Anonymous, Management of Natural Resources, Indonesia, 2010.
- [3] H. Suprianto, et al., "Potentials and constraints of water management measures for tidal lowlands in South Sumatra, Case study in a pilot area in Telang I. 9 th Inter-Regional Conference on Environment-Water," Delft, the Netherlands, 2006.
- [4] D. Software, "Mike-11 Reference Manual," ed: Danish Hydraulic Institute, Denmark, 2007.
- [5] E. Schultz, Land and Water Development: Finding a Balance Between Implementation, Management and Sustainability: International Institute for Infrastructural, *Hydraulic and Environmental Engineering*, 1993.
- [6] S. Munir, Role of Sediment Transport in Operation and Maintenance of Supply and Demand Based Irrigation Canals: Application to Machai Maira Branch Canals: UNESCO-IHE PhD Thesis: CRC Press, 2011.

180